





|                |                      |                    |                    |
|----------------|----------------------|--------------------|--------------------|
| Power          | <b>6 W</b>           | Voltage            | <b>230 V</b>       |
| Luminous flux* | <b>520 lm (120°)</b> | Colour temperature | <b>3000-6500 K</b> |
| Light colour   | <b>CCT</b>           | Beam angle         | <b>120 °</b>       |
| IK             | <b>06</b>            | Protection class   | <b>IP20</b>        |



 User manual



 Declaration of Conformity



 Photometric file



**Technical data:**

|                              |                |
|------------------------------|----------------|
| Product code                 | SLI038018CCT   |
| Power                        | 6 W            |
| Nominal current              | 40 mA          |
| Voltage                      | 230 V          |
| Energy efficiency classe     | F              |
| Energy consumption           | 6 kWh/1000h    |
| Frequency                    | 50HZ Hz        |
| Protection class             | II             |
| Useful luminous flux*        | 520 lm (120°)  |
| Luminous flux**              | 520 lm (360°)  |
| Light efficiency             | 87 lm/W        |
| Colour temperature           | 3000-6500 K    |
| Light colour                 | CCT            |
| Beam angle                   | 120 °          |
| RA                           | 80             |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | SMART          |
| Working temperature range    | -20/+40 °      |
| Lifespan                     | 17000 h        |
| Housing material             | PLASTIC, STEEL |
| IK                           | 06             |
| Protection class             | IP20           |
| Colour                       | White          |
| Dimension (axbxc)            | 112x112x35 mm  |
| Mounting hole                | 105x105 mm     |
| For use                      | Inside         |
| Assembly method              | Recessed       |
| Application                  | INT            |
| Made in                      | PRC            |



\*Applies to the LED source used. \*\*Luminaire luminous flux