



Power	<b>12 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1150 lm (120°)</b>	Colour temperature	<b>3000-6500 K</b>
Light colour	<b>CCT</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Protection class	<b>IP20</b>



 User manual



 Declaration of Conformity



 Photometric file



**Technical data:**

Product code	SLI038019CCT
Power	12 W
Nominal current	110 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Useful luminous flux*	1150 lm (120°)
Luminous flux**	1150 lm (360°)
Light efficiency	96 lm/W
Colour temperature	3000-6500 K
Light colour	CCT
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC, STEEL
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	162x162x35 mm
Mounting hole	155x155 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux