





CE

| | | | |
|------------------|-----------------------|--------------------|---------------|
| Power | 15 W | Voltage | 230 V |
| Luminous flux* | 1800 lm (360°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 150 ° |
| Protection class | IP44 | | |



See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|-------------------|
| Product code | SLI043017WW_PW |
| Power | 15 W |
| Nominal current | 115 mA |
| Voltage | 230 V |
| Energy consumption | 15 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.6 |
| Useful luminous flux* | 1800 lm (360°) |
| Luminous flux** | 1600 lm (360°) |
| Light efficiency | 120 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 150 ° |
| RA | >80 |
| Light source included | + |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 +40 ° |
| Lifespan | 17000 h |
| Housing material | TWORZYWO SZTUCZNE |
| Protection class | IP44 |
| Colour | White |
| Dimension (axbxc) | 596x46x63 mm |
| For use | Inside |
| Assembly method | On the ceiling |
| Application | Inside |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux