



CE

---

Power	<b>36 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>6300 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
UGR	<b>22</b>	IK	<b>08</b>

---



 User manual



 Declaration of Conformity

**Technical data:**

Product code	SLI047006NW_PW
Power	36 W
Nominal current	165 mA
Voltage	230 V
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.95
Useful luminous flux*	6300 lm (360°)
Luminous flux**	5200 lm (360°)
Light efficiency	175 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
UGR	22
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-30/+40 °
Lifespan	50000 h
Housing material	plastic
IK	08
Protection class	IP66
Colour	Gray/White
Dimension (axbxc)	1700x65x67 mm
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	L80B10 50000h MTBF 80000h ,



\*Applies to the LED source used. \*\*Luminaire luminous flux